

## Banana Silk Velvet

EN	DE	NL	FR	
Composition	Herstellungsverfahren	Productie methode	Composition	Handwoven
Pile material	Polmaterial	Poolmateriaal	Composition du velours	100% Banana Silk
Secondary backing	Beschichtung	Rug	Dossier	Cotton Cloth
Pile heigth	Polhöhe	Poolhoogte	Hauteur du velours	ca. 10 mm
Total heigth	Gesamthöhe	Totaal hoogte	Epaisseur totale	ca. 14 mm
Pile weigth	Polgewicht	Poolgewicht	Poids du velours	ca. 4200 g/m2
Total weigth	Gesamtgewicht	Totaal gewicht	Poids total	ca. 5500 g/m2

This sample may not be from the same dye batch as current stocks and should be used only as a guide. Matching:

Equal matching between widths cannot be guaranteed.

Installation: Professional installation is recommended and essential to a good quality underlay. Areas that might

receive prolonged exposure to direct sunlight should be protected by the use of blinds or curtains.

Cleaning: Professional cleaning recommended.

Maintenance: To maintain your carpets appearance it is recommended that it is vacuumed at least three times per week to

remove particles of dirt and dust, using an upright vacuum cleaner with a rotating brush.

It should be noted that overtime foot traffic will flatten the pile in main walkways causing areas of differential wear. This can cause the carpet to show areas of light and dark shading, this happens to all quality carpets

and would not be accepted as a basis for any complaint.