

# Toscane

| EN                | DE                    | NL                        | FR                     |                                            |
|-------------------|-----------------------|---------------------------|------------------------|--------------------------------------------|
| Composition       | Herstellungsverfahren | Productie methode         | Composition            | <b>Handwoven</b>                           |
| Width             | Breite                | Breedte                   | Largeur                | <b>4 &amp; 5 mtr</b>                       |
| Pile material     | Polmaterial           | Poolmateriaal             | Composition du velours | <b>70% Pet + 30% Wool</b>                  |
| Secondary backing | Beschichtung          | Rug                       | Dossier                | <b>Cotton Fabric Backing</b>               |
| Pile heigth       | Polhöhe               | Poolhoogte                | Hauteur du velours     | <b>ca. 6 mm</b>                            |
| Total heigth      | Gesamthöhe            | Totaal hoogte             | Epaisseur totale       | <b>ca. 8 mm</b>                            |
| Pile weigth       | Polgewicht            | Poolgewicht               | Poids du velours       | <b>ca. 1900 g / m2</b>                     |
| Total weigth      | Gesamtgewicht         | Totaal gewicht            | Poids total            | <b>ca. 3100 g / m2</b>                     |
| User rating       | Nutzung               | Gebruiksclassificatie     | Classification         | <b>Heavy Domestic / General Commercial</b> |
| Comfort rating    | Komfort               | Comfortklasse             | Niveau de confort      | <b>LC 1</b>                                |
| Anti static       | Antistatisch          | Electrostatisch gedrag    | Antistatique           | <b>Anti static</b>                         |
| Colour fastness   | Echtheid der farben   | Lichtechtheid             | Solidite de la couleur | <b>6</b>                                   |
| TOG rating        | Fusbodenheizung       | Thermische weerstand      | Resistance thermique   | <b>1.35</b>                                |
| Flammability      | Brennverhalten        | Brandgedrag               | Comportement au Ffeu   | <b>Cfl-S1</b>                              |
| Stairs            | Treppen               | Geschiktheid voor trappen | Escaliers              | <b>Yes</b>                                 |
| Bespoke available | Abgepasst             | Maatwerk beschikbaar      | Sur mesure             | <b>Yes</b>                                 |



**Matching:** This sample may not be from the same dye batch as current stocks and should be used only as a guide. Equal matching between widths cannot be guaranteed.

**Installation:** Professional installation is recommended and essential to a good quality underlay. Areas that might receive prolonged exposure to direct sunlight should be protected by the use of blinds or curtains.

**Cleaning:** Professional cleaning recommended.

**Maintenance:** To maintain your carpets appearance it is recommended that it is vacuumed at least three times per week to remove particles of dirt and dust, using an upright vacuum cleaner with a rotating brush. It should be noted that overtime foot traffi c will fl atten the pile in main walkways causing areas of differential wear. This can cause the carpet to show areas of light and dark shading, this happens to all quality carpets and would not be accepted as a basis for any complaint.